

## Local Defects - General

Heading : **Splítka Jindřichův Hradec**

Limits for : **AL Level 1; IL Level 2; IAL Level 3;**

Subheading : **od KV17**

KM From To : **27.350000 - 29.376250 [km]**

Date, Time : **16/5/2023, 10:06**

User text :

Orientation : **Forward**

(1) 27.350 km - 29.376 km [SZ 0 : 0 < V < 80 km/h]

| KM [km]         | Ga       | Tw1      | Al_dyn_L_1 | Al_dyn_R_2 | Cant     | Tp_L     | Tp_R     |                            |
|-----------------|----------|----------|------------|------------|----------|----------|----------|----------------------------|
| 1 - AL Level 1  | -7 / 25  | -8 / 8   | -12 / 12   | -12 / 12   | -16 / 16 | -12 / 12 | -12 / 12 |                            |
| 2 - IL Level 2  | -9 / 30  | -10 / 10 | -15 / 15   | -15 / 15   | -18 / 18 | -15 / 15 | -15 / 15 |                            |
| 3 - IAL Level 3 | -11 / 35 | -14 / 14 | -22 / 22   | -22 / 22   | -20 / 20 | -22 / 22 | -22 / 22 |                            |
| 27.350000       |          |          | 0-13.3/1   |            |          |          |          |                            |
| 27.350000       |          |          |            | 0-13.3/1   |          |          |          |                            |
| 27.354500       |          |          | 33+154.1/3 |            |          |          |          |                            |
| 27.354500       |          |          |            | 33+153.4/3 |          |          |          |                            |
| 27.365000       |          |          |            |            |          |          |          | Frog Swith 17 (17)         |
| 27.384750       |          |          |            |            |          |          |          | Tongue Switch 22           |
| 27.390000       |          |          | 29-132.4/3 |            |          |          |          |                            |
| 27.390000       |          |          |            | 29-135.3/3 |          |          |          |                            |
| 27.442750       |          |          | 28+51.0/3  |            |          |          |          |                            |
| 27.442750       |          |          |            | 28+51.8/3  |          |          |          |                            |
| 27.450750       |          | 1+9.1/1  |            |            |          |          |          |                            |
| 27.484500       |          |          | 20-28.1/3  |            |          |          |          |                            |
| 27.484750       |          |          |            | 20-27.8/3  |          |          |          |                            |
| 27.534250       |          |          |            | 14+14.4/1  |          |          |          |                            |
| 27.601500       |          |          | 8-14.4/1   |            |          |          |          |                            |
| 27.603250       |          |          |            | 8-15.0/1   |          |          |          |                            |
| 27.638000       |          |          |            | 9+13.5/1   |          |          |          |                            |
| 27.638250       |          |          | 7+12.8/1   |            |          |          |          |                            |
| 27.688750       |          |          | 17-37.5/3  |            |          |          |          |                            |
| 27.688750       |          |          |            | 18-39.4/3  |          |          |          |                            |
| 27.694750       |          |          |            |            |          |          |          | KM 27.7                    |
| 27.718250       |          |          |            | 20+36.5/3  |          |          |          |                            |
| 27.719000       |          |          | 19+34.4/3  |            |          |          |          |                            |
| 27.753250       |          |          |            | 8-14.0/1   |          |          |          |                            |
| 27.756250       |          |          | 3-12.3/1   |            |          |          |          |                            |
| 27.793750       |          |          | 14-19.8/2  |            |          |          |          |                            |
| 27.794750       |          |          |            | 12-18.2/2  |          |          |          |                            |
| 27.835000       |          |          | 8+24.8/3   |            |          |          |          |                            |
| 27.836000       |          |          |            | 6+23.4/3   |          |          |          |                            |
| 28.079250       |          |          |            | 18-13.5/1  |          |          |          |                            |
| 28.079500       |          |          | 19-13.4/1  |            |          |          |          |                            |
| 28.099250       |          |          |            |            |          |          |          | Level crossing (28.108250) |
| 28.129250       |          |          | 9+23.3/3   |            |          |          |          |                            |
| 28.131250       |          |          |            | 6+22.6/3   |          |          |          |                            |
| 28.162000       |          |          |            | 14-29.4/3  |          |          |          |                            |
| 28.162250       |          |          | 14-28.4/3  |            |          |          |          |                            |
| 28.269750       |          |          |            | 15-18.7/2  |          |          |          |                            |
| 28.271000       |          |          | 15-18.3/2  |            |          |          |          |                            |
| 28.303000       |          |          | 16+20.8/2  |            |          |          |          |                            |
| 28.303500       |          |          |            | 15+20.2/2  |          |          |          |                            |
| 28.629500       |          |          | 3-12.1/1   |            |          |          |          |                            |
| 28.651750       |          |          | 12+19.4/2  |            |          |          |          |                            |

|                    |         |          |           |            |         |         |         |                      |
|--------------------|---------|----------|-----------|------------|---------|---------|---------|----------------------|
| 28.652000          |         |          |           | 10+18.5/2  |         |         |         |                      |
| 28.682750          |         |          | 7-16.8/2  |            |         |         |         |                      |
| 28.685000          |         |          |           | 4-15.7/2   |         |         |         |                      |
| 28.703500          |         |          | 8+14.3/1  |            |         |         |         |                      |
| 28.704250          |         |          |           | 7+14.0/1   |         |         |         |                      |
| 28.730750          |         |          | 10-25.1/3 |            |         |         |         |                      |
| 28.730750          |         |          |           | 10-24.8/3  |         |         |         |                      |
| 28.756250          |         |          | 22+49.1/3 |            |         |         |         |                      |
| 28.756500          |         |          |           | 22+48.6/3  |         |         |         |                      |
| 28.787500          |         |          |           |            |         |         |         | Crossing (28.788000) |
| 28.802500          |         |          |           |            |         |         |         | Tongue Switch 23     |
| 28.804250          |         |          | 26-59.0/3 |            |         |         |         |                      |
| 28.804500          |         |          |           | 26-58.7/3  |         |         |         |                      |
| 28.820500          |         |          |           |            |         |         |         | Frog Switch 23       |
| 28.824000          |         |          |           |            |         |         |         | End of Switch 23     |
| 28.836250          |         |          | 26+64.3/3 |            |         |         |         |                      |
| 28.836250          |         |          |           | 26+63.1/3  |         |         |         |                      |
| 28.887250          |         |          | 10-24.2/3 |            |         |         |         |                      |
| 28.888000          |         |          |           | 7-22.5/3   |         |         |         |                      |
| 28.911250          |         |          | 6+17.0/2  |            |         |         |         |                      |
| 28.913000          |         |          |           | 2+15.5/2   |         |         |         |                      |
| 28.972250          |         |          | 8-15.0/1  |            |         |         |         |                      |
| 28.972500          |         |          |           | 8-14.2/1   |         |         |         |                      |
| 28.992000          |         |          | 18+43.3/3 |            |         |         |         |                      |
| 28.992000          |         |          |           | 18+42.1/3  |         |         |         |                      |
| 28.997000          |         |          |           |            |         |         |         | KM 29.000            |
| 29.018500          |         |          | 22-48.0/3 |            |         |         |         |                      |
| 29.018500          |         |          |           | 22-47.5/3  |         |         |         |                      |
| 29.060250          |         |          |           | 20+28.6/3  |         |         |         |                      |
| 29.060500          |         |          | 21+28.7/3 |            |         |         |         |                      |
| 29.089500          |         | 1+11.5/2 |           |            |         |         |         |                      |
| 29.095500          |         |          |           |            |         |         |         | KM 29.1              |
| 29.100250          |         |          | 12-27.1/3 |            |         |         |         |                      |
| 29.100750          |         |          |           | 12-27.0/3  |         |         |         |                      |
| 29.196250          |         |          |           |            |         |         |         | KM 29.2              |
| 29.215750          |         |          |           | 8+16.8/2   |         |         |         |                      |
| 29.218000          |         |          | 4+15.4/2  |            |         |         |         |                      |
| 29.247000          |         |          | 14-30.2/3 |            |         |         |         |                      |
| 29.248000          |         |          |           | 12-27.7/3  |         |         |         |                      |
| 29.279500          |         |          | 10+25.1/3 |            |         |         |         |                      |
| 29.280500          |         |          |           | 8+23.9/3   |         |         |         |                      |
| 29.295750          |         |          |           |            |         |         |         | KM 29.3              |
| 29.346500          | 1-7.2/1 |          |           |            |         |         |         |                      |
| 29.355000          | 1-9.7/2 |          |           |            |         |         |         |                      |
| 29.356000          |         |          | 14-21.4/2 |            |         |         |         |                      |
| 29.357500          |         |          |           | 13-21.6/2  |         |         |         |                      |
|                    |         |          |           |            |         |         |         |                      |
|                    |         |          |           |            |         |         |         |                      |
| Summary of Defects |         |          |           |            |         |         |         |                      |
|                    | Ga      | Tw1      | Al_dyn_L  | Al_dyn_R_2 | Cant    | Tp_L    | Tp_R    | Grand Total Defect   |
| Over limit 1       | 0.00 km | 0.00 km  | 0.06 km   | 0.07 km    | 0.00 km | 0.00 km | 0.00 km | 0.08 km              |
| Over limit 1 [%]   | 0.05%   | 0.06%    | 2.81%     | 3.54%      | 0.00%   | 0.00%   | 0.00%   | 4.03 %               |
| Over limit 2       | 0.00 km | 0.00 km  | 0.09 km   | 0.08 km    | 0.00 km | 0.00 km | 0.00 km | 0.09 km              |
| Over limit 2 [%]   | 0.04%   | 0.05%    | 4.33%     | 4.00%      | 0.00%   | 0.00%   | 0.00%   | 4.68 %               |
| Over limit 3       | 0.00 km | 0.00 km  | 0.37 km   | 0.36 km    | 0.00 km | 0.00 km | 0.00 km | 0.37 km              |
| Over limit 3 [%]   | 0.00%   | 0.00%    | 18.19%    | 17.63%     | 0.00%   | 0.00%   | 0.00%   | 18.35 %              |